

Exhibit 1



US008266749B2

(12) **United States Patent**
Dua et al.

(10) **Patent No.:** **US 8,266,749 B2**
(45) **Date of Patent:** ***Sep. 18, 2012**

(54) **ARTICLE OF FOOTWEAR HAVING A TEXTILE UPPER**

(75) Inventors: **Bhupesh Dua**, Portland, OR (US);
Edward Nathaniel Thomas, Portland, OR (US)

(73) Assignee: **Nike, Inc.**, Beaverton, OR (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

1,910,251 A	5/1933	Joha	
2,001,293 A	5/1935	Wallace	
2,047,724 A	7/1936	Zuckerman	
2,147,197 A	11/1936	Glidden	
2,314,098 A	3/1943	McDonald	
2,330,199 A	9/1943	Basch	
2,400,692 A	5/1946	Herbert	
2,467,237 A *	4/1949	Sherman et al.	12/142 G
2,538,673 A	1/1951	Donahue	
2,586,045 A	2/1952	Hoza	
2,641,004 A	6/1953	Ronyan et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1067566 1/1993

(Continued)

(21) Appl. No.: **13/236,742**

(22) Filed: **Sep. 20, 2011**

(65) **Prior Publication Data**

US 2012/0005922 A1 Jan. 12, 2012

Related U.S. Application Data

(60) Continuation of application No. 12/879,517, filed on Sep. 10, 2010, now Pat. No. 8,042,288, which is a continuation of application No. 12/032,995, filed on Feb. 18, 2008, now Pat. No. 7,814,598, which is a division of application No. 10/791,289, filed on Mar. 3, 2004, now Pat. No. 7,347,011.

(51) **Int. Cl.**
A43D 8/00 (2006.01)

(52) **U.S. Cl.** **12/146 C; 36/45**

(58) **Field of Classification Search** **12/146 C, 12/142 G; 36/45, 10, 55, 3 A**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,597,934 A	8/1926	Stimpson
1,888,172 A	6/1932	Joha
1,902,780 A	3/1933	Holden et al.

21 Claims, 12 Drawing Sheets

OTHER PUBLICATIONS

Santoni S.p. A. publication: Knitting Wear, SM8 Top 1 (2 pages).


(Continued)

Primary Examiner — Marie Patterson

(74) *Attorney, Agent, or Firm* — Banner & Witcoff, Ltd.

(57) **ABSTRACT**

An article of footwear and a method of manufacturing the article of footwear are disclosed. The footwear may include an upper and a sole structure. The upper incorporates a textile element with edges that are joined together to define at least a portion of a void for receiving a foot. The textile element may also have a first area and a second area with a unitary construction. The first area is formed of a first stitch configuration, and the second area is formed of a second stitch configuration that is different from the first stitch configuration to impart varying textures to a surface of the textile element. Various warp knitting or weft knitting processes may be utilized to form the textile element.



US 8,266,749 B2

Page 2

U.S. PATENT DOCUMENTS

2,675,631	A	4/1954	Doughty
2,701,458	A	2/1955	Ducharme
3,694,940	A	10/1972	Stohr
4,211,806	A	7/1980	Civardi et al.
4,255,949	A	3/1981	Thorneburg
4,276,671	A	7/1981	Melton
4,317,292	A	3/1982	Melton
4,373,361	A	2/1983	Thorneburg
4,447,967	A	5/1984	Zaino
4,607,439	A	8/1986	Harada
4,785,558	A	11/1988	Shiomura
4,813,158	A	3/1989	Brown
4,852,272	A	8/1989	Chilewich et al.
5,095,720	A	3/1992	Tibbals, Jr.
5,323,627	A	6/1994	Lonati et al.
5,345,638	A	9/1994	Nishida
5,353,524	A	10/1994	Brier
5,461,884	A	10/1995	McCartney et al.
5,511,323	A	4/1996	Dahlgren
5,735,145	A	4/1998	Pernick
5,746,013	A	5/1998	Fay, Sr.
6,308,438	B1	10/2001	Throneburg et al.
6,558,784	B1	5/2003	Norton et al.
6,910,288	B2	6/2005	Dua
6,931,762	B1	8/2005	Dua
7,016,867	B2	3/2006	Lyden
7,051,460	B2	5/2006	Orei et al.
7,107,235	B2	9/2006	Lyden

7,207,196	B2	4/2007	Lonati et al.
7,347,011	B2	3/2008	Dua et al.
7,814,598	B2	10/2010	Dua et al.
2002/0078599	A1	6/2002	Delgorgue et al.
2003/0126762	A1	7/2003	Tseng
2004/0118018	A1	6/2004	Dua

FOREIGN PATENT DOCUMENTS

CN	1411762	4/2003
CN	1429512	7/2003
DE	627878	3/1936
EP	1437057	7/2004
GB	1539886	2/1979
WO	90/03744	4/1990

OTHER PUBLICATIONS

International Search Report and Written Opinion mailed on May 19, 2005 in related PCT Application No. PCT/US2005/004776.

Page 1 of Lyden Letter of Apr. 21, 2010—Redacted.

Office Action issued Jul. 27, 2007 in corresponding Chinese Patent Application No. 2005800066703, and English translation thereof.

Office Action issued Feb. 15, 2008 in corresponding Chinese Patent Application No. 2005800066703, and English translation thereof.

Office Action issued Jun. 13, 2008 in corresponding Chinese Patent Application No. 2005800066703, and English translation thereof.


* cited by examiner

U.S. Patent

Sep. 18, 2012

Sheet 1 of 12

US 8,266,749 B2





U.S. Patent


Sep. 18, 2012

Sheet 2 of 12

US 8,266,749 B2







U.S. Patent

Sep. 18, 2012

Sheet 5 of 12

US 8,266,749 B2




Figure 6




Figure 7




Figure 8

U.S. Patent

Sep. 18, 2012

Sheet 7 of 12

US 8,266,749 B2




Figure 9




Figure 10




Figure 11





Figure 12






Figure 14

US 8,266,749 B2

1

**ARTICLE OF FOOTWEAR HAVING A
TEXTILE UPPER****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This U.S. patent application is a continuation application of and claims priority to U.S. patent application Ser. No. 12/879,517, filed Sep. 10, 2010, which is a continuation application of and claims priority to U.S. patent application Ser. No. 12/032,995, filed Feb. 18, 2008, which is a divisional application of and claims priority to U.S. patent application Ser. No. 10/791,289, filed Mar. 3, 2004, now U.S. Pat. No. 7,347,011, issued Mar. 25, 2008, each of which are being entirely incorporated herein by reference.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to footwear. The invention concerns, more particularly, an article of footwear incorporating an upper that is at least partially formed from a textile material.

2. Description of Background Art

Conventional articles of athletic footwear include two primary elements, an upper and a sole structure. The upper provides a covering for the foot that securely receives and positions the foot with respect to the sole structure. In addition, the upper may have a configuration that protects the foot and provides ventilation, thereby cooling the foot and removing perspiration. The sole structure is secured to a lower surface of the upper and is generally positioned between the foot and the ground. In addition to attenuating ground reaction forces and absorbing energy (i.e., imparting cushioning), the sole structure may provide traction and control potentially harmful foot motion, such as over pronation. Accordingly, the upper and the sole structure operate cooperatively to provide a comfortable structure that is suited for a wide variety of ambulatory activities, such as walking and running. The general features and configuration of the conventional upper are discussed in greater detail below.

The upper forms a void on the interior of the footwear for receiving the foot. The void has the general shape of the foot, and access to the void is provided by an ankle opening. Accordingly, the upper extends over the instep and toe areas of the foot, along the medial and lateral sides of the foot, and around the heel area of the foot. A lacing system is often incorporated into the upper to selectively increase the size of the ankle opening and permit the wearer to modify certain dimensions of the upper, particularly girth, to accommodate feet with varying proportions. In addition, the upper may include a tongue that extends under the lacing system to enhance the comfort of the footwear, and the upper may include a heel counter to limit movement of the heel.

Various materials may be utilized in manufacturing the upper. The upper of an article of athletic footwear, for example, may be formed from multiple material layers that include an exterior layer, an intermediate layer, and an interior layer. The materials forming the exterior layer of the upper may be selected based upon the properties of wear-resistance, flexibility, and air-permeability, for example. With regard to the exterior layer, the toe area and the heel area may be formed of leather, synthetic leather, or a rubber material to impart a relatively high degree of wear-resistance. Leather, synthetic leather, and rubber materials may not exhibit the desired degree of flexibility and air-permeability. Accordingly, various other areas of the exterior layer of the upper

2

may be formed from a synthetic or natural textile. The exterior layer of the upper may be formed, therefore, from numerous material elements that each impart different properties to specific portions of the upper.

5 An intermediate layer of the upper may be formed from a lightweight polymer foam material that provides cushioning and protects the foot from objects that may contact the upper. Similarly, an interior layer of the upper may be formed of a moisture-wicking textile that removes perspiration from the area immediately surrounding the foot. In some articles of athletic footwear, the various layers may be joined with an adhesive, and stitching may be utilized to join elements within a single layer or to reinforce specific areas of the upper.

10 Although the materials selected for the upper vary significantly, textile materials often form at least a portion of the exterior layer and interior layer. A textile may be defined as any manufacture from fibers, filaments, or yarns characterized by flexibility, fineness, and a high ratio of length to thickness. Textiles generally fall into two categories. The first category includes textiles produced directly from webs of filaments or fibers by randomly interlocking to construct non-woven fabrics and felts. The second category includes textiles formed through a mechanical manipulation of yarn, thereby producing a woven fabric, for example.

15 Yarn is the raw material utilized to form textiles in the second category. In general, yarn is defined as an assembly having a substantial length and relatively small cross-section that is formed of at least one filament or a plurality of fibers. Fibers have a relatively short length and require spinning or twisting processes to produce a yarn of suitable length for use in textiles. Common examples of fibers are cotton and wool. Filaments, however, have an indefinite length and may merely be combined with other filaments to produce a yarn suitable for use in textiles. Modern filaments include a plurality of synthetic materials such as rayon, nylon, polyester, and polyacrylic, with silk being the primary, naturally-occurring exception. Yarn may be formed of a single filament, which is conventionally referred to as a monofilament yarn, or a plurality of individual filaments grouped together. Yarn may also include separate filaments formed of different materials, or the yarn may include filaments that are each formed of two or more different materials. Similar concepts also apply to yarns formed from fibers. Accordingly, yarns may have a variety of configurations that generally conform to the definition provided above.

20 The various techniques for mechanically manipulating yarn into a textile include interweaving, intertwining and twisting, and interlooping. Interweaving is the intersection of two yarns that cross and interweave at right angles to each other. The yarns utilized in interweaving are conventionally referred to as warp and weft. Intertwining and twisting encompasses procedures such as braiding and knotting where yarns intertwine with each other to form a textile. Interlooping involves the formation of a plurality of columns of intermeshed loops, with knitting being the most common method of interlooping.

25 The textiles utilized in footwear uppers generally provide a lightweight, air-permeable structure that is flexible and comfortably receives the foot. In order to impart other properties to the footwear, including durability and stretch-resistance, additional materials are commonly combined with the textile, including leather, synthetic leather, or rubber, for example. With regard to durability, U.S. Pat. No. 4,447,967 to Zaino discloses an upper formed of a textile material that has a polymer material injected into specific zones to reinforce the zones against abrasion or other forms of wear. Regarding stretch resistance, U.S. Pat. No. 4,813,158 to Brown and U.S.

US 8,266,749 B2

3

Pat. No. 4,756,098 to Boggia both disclose a substantially inextensible material that is secured to the upper, thereby limiting the degree of stretch in specific portions of the upper.

From the perspective of manufacturing, utilizing multiple materials to impart different properties to an article of footwear may be an inefficient practice. For example, the various materials utilized in a conventional upper are not generally obtained from a single supplier. Accordingly, a manufacturing facility must coordinate the receipt of specific quantities of materials with multiple suppliers that may have distinct business practices or may be located in different regions or countries. The various materials may also require additional machinery or different assembly line techniques to cut or otherwise prepare the material for incorporation into the footwear. In addition, incorporating separate materials into an upper may involve a plurality of distinct manufacturing steps requiring multiple individuals. Employing multiple materials, in addition to textiles, may also detract from the breathability of footwear. Leather, synthetic leather, or rubber, for example, are not generally permeable to air. Accordingly, positioning leather, synthetic leather, or rubber on the exterior of the upper may inhibit air flow through the upper, thereby increasing the amount of perspiration, water vapor, and heat trapped within the upper and around the foot.

SUMMARY OF THE INVENTION

The present invention is an upper for an article of footwear, the upper incorporating a textile element formed with a knitting machine, for example. In one aspect of the invention, the textile element has edges that are joined together to define at least a portion of a void for receiving a foot. In another aspect of the invention, the textile element has a first area and a second area of unitary construction. The first area is formed of a first stitch configuration, and the second area is formed of a second stitch configuration that is different from the first stitch configuration to impart varying textures to a surface of the textile element. The knitting machine may have a configuration that forms the textile element through either warp knitting or weft knitting.

Another aspect of the invention involves a method of manufacturing an article of footwear. The method includes a step of mechanically-manipulating a yarn with a circular knitting machine, for example, to form a cylindrical textile structure. In addition, the method involves removing at least one textile element from the textile structure, and incorporating the textile element into an upper of the article of footwear.

In another aspect of the invention, an article of footwear has an upper and a sole structure secured to the upper. The upper incorporates a textile element formed with a knitting machine. The textile element is removed from a textile structure that includes an outline of the textile element, and the textile element has edges that are joined together to define at least a portion of a void for receiving a foot.

The advantages and features of novelty characterizing the present invention are pointed out with particularity in the appended claims. To gain an improved understanding of the advantages and features of novelty, however, reference may be made to the following descriptive matter and accompanying drawings that describe and illustrate various embodiments and concepts related to the invention.

DESCRIPTION OF THE DRAWINGS

The foregoing Summary of the Invention, as well as the following Detailed Description of the Invention, will be better understood when read in conjunction with the accompanying drawings.

4

FIG. 1 is a lateral elevational view of an article of footwear having an upper in accordance with the present invention.

FIG. 2 is a lateral elevational view of the upper.

FIG. 3 is a top plan view of the upper.

FIG. 4 is a rear elevational view of the upper.

FIG. 5 is a bottom plan view of the upper.

FIG. 6 is a first cross-sectional view of the upper, as defined by section line 6-6 in FIG. 2.

FIG. 7 is a second cross-sectional view of the upper, as defined by section line 7-7 in FIG. 2.

FIG. 8 is a plan view of a textile element that forms at least a portion of the upper.

FIG. 9 is a perspective view of a textile structure that incorporates two of the textile element.

FIG. 10 is a plan view of another textile element.

FIG. 11 is a plan view of yet another textile element.

FIG. 12 is a lateral elevational view of another article of footwear having an upper in accordance with the present invention.

FIG. 13 is a lateral elevational view of yet another article of footwear having an upper in accordance with the present invention.

FIG. 14 is a cross-sectional view of the footwear depicted in FIG. 13, as defined by section line 14-14.

DETAILED DESCRIPTION OF THE INVENTION

The following discussion and accompanying figures disclose an article of footwear **10** and a method of manufacturing footwear **10**, or components thereof, in accordance with the present invention. Footwear **10** is depicted in the figures and discussed below as having a configuration that is suitable for athletic activities, particularly running. The concepts disclosed with respect to footwear **10** may, however, be applied to footwear styles that are specifically designed for a variety of other athletic activities, including basketball, baseball, football, soccer, walking, and hiking, for example, and may also be applied to various non-athletic footwear styles. Accordingly, one skilled in the relevant art will recognize that the concepts disclosed herein may be applied to a wide range of footwear styles and are not limited to the specific embodiments discussed below and depicted in the figures.

The primary elements of footwear **10** are depicted in FIG. 1 as being a sole structure **20** and an upper **30**. Sole structure **20** is secured to a lower portion of upper **30** and provides a durable, wear-resistant component that imparts cushioning as footwear **10** impacts the ground. Upper **30** is at least partially formed from a textile element **40** that defines an interior void for comfortably receiving a foot and securing a position of the foot relative to sole structure **20**. Various edges of textile element **40** are then secured together to form the shape of upper **30**. In some embodiments, textile element **40** may form substantially all of upper **30**, or textile element **40** may only be a portion of an upper.

Sole structure **20** has a generally conventional configuration that includes a midsole **21** and an outsole **22**. Midsole **21** is secured to a lower portion of upper **30** and is formed of a polymer foam material, such as ethylvinylacetate or polyurethane. Accordingly, midsole **21** attenuates ground reaction forces and absorbs energy (i.e., provides cushioning) as sole structure **20** impacts the ground. To enhance the force attenuation and energy absorption characteristics of sole structure **20**, midsole **21** may incorporate a fluid-filled bladder, as disclosed in U.S. Pat. Nos. 4,183,156 and 4,219,945 to Rudy. Alternately or in combination, midsole **21** may incorporate a plurality of discrete, columnar support elements, as disclosed in U.S. Pat. Nos. 5,343,639 and 5,353,523 to Kilgore et al.

US 8,266,749 B2

5

Outsole 22 is secured to a lower surface of midsole 21 and may be formed from carbon black rubber compound to provide a durable, wear-resistant surface for engaging the ground. Outsole 22 may also incorporate a textured lower surface to enhance the friction characteristics of footwear 10. In addition, footwear 10 may include an insole (not depicted), which is a relatively thin, cushioning member located within upper 30 and adjacent to a plantar surface of the foot for enhancing the comfort of footwear 10.

Sole structure 20 is described above as having the elements of a conventional sole structure for athletic footwear. Other footwear styles, including, dress shoes and boots, for example, may have other types of conventional sole structures specifically tailored for use with the respective types of footwear. In addition to a conventional configuration, however, sole structure 20 may also exhibit a unique, non-conventional structure. Accordingly, the particular configuration of sole structure 20 may vary significantly within the scope of the present invention to include a wide range of configurations, whether conventional or non-conventional.

Upper 30 is depicted in FIGS. 2-7 as having a lateral region 31, an opposite medial region 32, an instep region 33, a lower region 34, and a heel region 35. Lateral region 31 extends through a longitudinal length of footwear 10 and is generally configured to contact and cover a lateral side of the foot. Medial region 32 has a similar configuration that generally corresponds with a medial side of the foot. Instep region 33 is positioned between lateral region 31 and medial region 32, and instep region 33 extends over an instep area of the foot. Lower region 34 forms a bottom surface of upper 30 and also extends through the longitudinal length of footwear 10. Heel region 35 forms a rear portion of upper 30 and is generally configured to contact and cover a heel area of the foot. In addition, lateral region 31, medial region 32, instep region 33, and heel region 35 cooperatively define an ankle opening 36 for providing the foot with access to the void within upper 30.

Upper 30 is at least partially formed from textile element 40, which forms regions 31-35, and may also include laces or other elements associated with a conventional upper for footwear. Textile element 40 is a single material element that is formed to exhibit a unitary (i.e., one-piece) construction, and textile element 40 is formed or otherwise shaped to extend around the foot. As depicted in FIGS. 2-7, textile element 40 forms both an exterior surface and an interior surface of upper 30. Textile element 40 may be formed as a part of a larger textile element. Textile element 40 is then removed from the larger textile element and various edges of textile element 40 are secured together to form the shape of upper 30. A plurality of seams 51-54 are formed, therefore, when joining the edges of the textile element. Seam 51 extends along the longitudinal length of lower region 34 and is centrally-located with respect to lateral region 31 and medial region 32. Seam 52 is also centrally-located and extends upward along heel region 35. A seam 53 is positioned in a forefoot area of upper 30 and joins a portion of lower region 34 with both of lateral region 31 and medial region 32. In addition, a seam 54 is positioned in a rear area of upper 30 and joins a portion of lower region 34 with heel region 35.

Textile element 40 exhibits the general shape depicted in FIG. 8 prior to the formation of seams 51-54. Following formation of seams 51-54, however, textile element 40 exhibits the shape of upper 30 depicted in FIGS. 2-7. Seams 51-54 are formed by securing various edges of textile element 40 together. More specifically, (1) seam 51 is formed by securing an edge 41a with an edge 41b; (2) seam 52 is formed by securing an edge 42a with an edge 42b; (3) a first portion of seam 53 is formed by securing an edge 43a with an edge 43b

6

(4) a second portion of seam 53 is formed by securing an edge 43c with an edge 43d; (5) a first portion of seam 54 is formed by securing an edge 44a with an edge 44b; and (6) a second portion of seam 54 is formed by securing an edge 44c with an edge 44d. Referring to FIG. 8, the positions of regions 31-35 and ankle opening 36 are identified to provide a frame of reference relating to the various portions of textile element 40.

In order to join edges 41a and 41b to form seam 51, textile element 40 is folded or otherwise overlapped such that edge 41a is placed adjacent to edge 41b. Stitching, an adhesive, or heat bonding, for example, is then utilized to secure edge 41a and edge 41b. Textile element 40, as depicted in FIG. 8, has a generally planar configuration. Upon the formation of seam 51, however, one portion of textile element 40 overlaps the other portion of textile element 40. The volume between the overlapping portions effectively forms a portion of the void within upper 30 for receiving the foot.

The folding or overlapping of textile element 40 to form seam 51 places edge 42a adjacent to edge 42b, which facilitates the formation of seam 52. With reference to FIG. 8, an edge 45 forms a generally u-shaped area in textile element 40. Upon the joining of edges 42a and 42b to form seam 52, the u-shaped area becomes an aperture in textile element 40 and effectively forms ankle opening 36. Each of edges 43a-43d and edges 44a-44d are formed from a generally v-shaped area of textile element 40. Accordingly, seams 53 and 54 may be formed by closing the v-shaped areas and securing the various edges together.

Following the formation of each of seams 51-54, the manufacturing of upper 30 is essentially complete. Various finishing steps may be performed, such as reinforcing ankle opening 36, for example. Upper 30 (i.e., textile element 40) is then secured to sole structure 20, with an adhesive, for example. The insole is then placed into the void within upper 30 and adjacent to lower region 34. In some embodiments, various reinforcing members may be added to the exterior or interior surface of upper 20 in order to limit the degree of stretch in upper 20 or provide enhanced wear-resistance. In addition, a lacing system may be added to provide adjustability.

Textile element 40 is a single material element with a unitary construction, as discussed above. As defined for purposes of the present invention, unitary construction is intended to express a configuration wherein portions of a textile element are not joined together by seams or other connections, as depicted with textile element 40 in FIG. 8. Although the various edges 41a-44d are joined together to form seams 51-54, the various portions of textile element 40 are formed as an unitary element without seams, as discussed below.

Textile element 40 is primarily formed from one or more yarns that are mechanically-manipulated through either an interweaving, intertwining and twisting, or interlooping process, for example. As discussed in the Background of the Invention section above, interweaving is the intersection of two yarns that cross and interweave at right angles to each other. The yarns utilized in interweaving are conventionally referred to as warp and weft. Intertwining and twisting encompasses procedures such as braiding and knotting where yarns intertwine with each other to form a textile. Interlooping involves the formation of a plurality of columns of intermeshed loops, with knitting being the most common method of interlooping. Textile element 40 may, therefore, be formed from one of these processes for manufacturing a textile.

A variety of mechanical processes have been developed to manufacture a textile. In general, the mechanical processes may be classified as either warp knitting or weft knitting. With

US 8,266,749 B2

7

regard to warp knitting, various specific sub-types that may be utilized to manufacture a textile include tricot, raschel, and double needle-bar raschel (which further includes jacquard double needle-bar raschel). With regard to weft knitting, various specific sub-types that may be utilized to manufacture a textile include circular knitting and flat knitting. Various types of circular knitting include sock knitting (narrow tube), body garment (seamless or wide tube), and jacquard.

Textile element **40** may be formed through any of the mechanical processes discussed above. Accordingly, textile element **40** may be formed on either a warp knitting machine or a weft knitting machine. One suitable knitting machine for forming textile element **40** is a wide-tube circular knit jacquard machine. Another suitable knitting machine for forming textile element **40** is a wide-tube circular knitting machine that is produced in the Lonati Group by Santoni S.p.A. of Italy under the SM8 TOP1 model number. This Santoni S.p.A. wide-tube circular knitting machine may form a textile structure having a diameter that ranges from 10 inches to 20 inches, with 8 feeds for each diameter. The machine exhibits a maximum 140 revolutions per minute for 10 inch diameters, and a maximum 120 revolutions per minute for 13 inch diameters. Furthermore, the machine gauge is variable between 16, 22, 24, 26, 28, and 32 needles per inch, and is suitable for various needle gauges ranging from 48 to 75.

A wide-tube circular knitting machine, as produced by Santoni S.p.A., forms a generally cylindrical textile structure and is capable of forming various types of stitches within a single textile structure. In general, the wide-tube circular knitting machine may be programmed to alter the design on the textile structure through needle selection. That is, the type of stitch that is formed at each location on the textile structure may be selected by programming the wide-tube circular knitting machine such that specific needles either accept or do not accept yarn at each stitch location. In this manner, various patterns, textures, or designs may be selectively and purposefully imparted to the textile structure.

An example of a textile structure **60** that may be formed with a wide-tube circular knitting machine is depicted in FIG. 9. Textile structure **60** has a generally cylindrical configuration, and the types of stitches vary throughout textile structure **60** so that a pattern is formed with the outline of textile element **40**. That is, differences in the stitches within textile structure **60** form an outline with the shape and proportions of textile element **40**.

The Santoni S.p.A. wide-tube circular knitting machine may form a textile structure having a diameter that ranges from 10 inches to 16 inches, as discussed above. Assuming that textile structure **60** exhibits a diameter of 10 inches, then the circumference of textile structure **60** is approximately 31 inches. In many circumstances, the total width of textile element **40** will be approximately 12 inches, depending upon the size of footwear **10**. The outlines for at least two textile elements **40** may, therefore, be formed on textile structure **60**. Referring to FIG. 9, the outline of textile element **40** is depicted on a front portion of textile structure **60**, and the outline of another textile element **40** is depicted on a rear portion of textile structure **60**. Accordingly, a first textile element **40** and a second textile element **40** may be simultaneously formed in a single textile structure **60**. As the diameter of textile element **60** is increased or the width of textile element **40** decreases, however, an even greater number of textile elements **40** may be outlined on textile structure **60**.

Textile structure **60** may be formed with a wide-tube circular knitting machine, as discussed above. The types of stitches that form textile structure **60** may be varied to form an outline of one or more textile elements **40** on textile structure

8

60. That is, the wide-tube circular knitting machine may be programmed to form different types of stitches in textile structure **60** so as to outline one or more textile elements **40**. Each textile element **40** is then removed from textile structure **60** with a die-cutting, laser-cutting, or other conventional cutting operation. Once textile element **40** is removed from textile structure **60**, seams **51-54** may be formed and textile element **40** may be incorporated into footwear **10**.

The yarn forming textile element **40** may be generally defined as an assembly having a substantial length and relatively small cross-section that is formed of at least one filament or a plurality of fibers. Fibers have a relatively short length and require spinning or twisting processes to produce a yarn of suitable length for use in an interlooping process. Common examples of fibers are cotton and wool. Filaments, however, have an indefinite length and may merely be combined with other filaments to produce a yarn suitable for use in an interlooping process. Modern filaments include a plurality of synthetic materials such as rayon, nylon, polyester, and acrylic, with silk being the primary, naturally-occurring exception. Yarn may be formed of a single filament (conventionally referred to as a monofilament yarn) or a plurality of individual filaments. Yarn may also be formed of separate filaments formed of different materials, or the yarn may be formed of filaments that are each formed of two or more different materials. Similar concepts also apply to yarns formed from fibers. Accordingly, yarns may have a variety of configurations within the scope of the present invention that generally conform to the definition provided above.

In order to provide the stretch and recovery properties to upper **30**, and particularly textile element **40**, a yarn that incorporates an elastane fiber may be utilized. Elastane fibers are available from E.I. duPont de Nemours Company under the LYCRA trademark. Such fibers may have the configuration of covered LYCRA, wherein the fiber includes a LYCRA core that is surrounded by a nylon sheath. One suitable yarn, for example, includes a 70 denier elastane core that is covered with nylon having a 2 ply, 80 denier, 92 filament structure. Other fibers or filaments exhibiting elastic properties may also be utilized.

As discussed above, a yarn that incorporates elastane fibers is suitable for textile element **40**. A plurality of other yarns, whether elastic or inelastic, are also suitable for textile element **40**. The characteristics of the yarn selected for textile element **40** depend primarily upon the materials that form the various filaments and fibers. Cotton, for example, provides a soft hand, natural aesthetics, and biodegradability. Elastane fibers, as discussed above, provide substantial stretch and recoverability. Rayon provides high luster and moisture absorption. Wool also provides high moisture absorption, in addition to insulating properties. Polytetrafluoroethylene coatings may provide a low friction contact between the textile and the skin. Nylon is a durable and abrasion-resistant material with high strength. Finally, polyester is a hydrophobic material that also provides relatively high durability. Accordingly, the materials comprising the yarn may be selected to impart a variety of physical properties to textile element **40**, and the physical properties may include, for example, strength, stretch, support, stiffness, recovery, fit, and form.

Textile element **40** is depicted as having a generally smooth, non-varied stitch configuration. That is, similar stitches are utilized throughout textile element **40** to impart a common texture to the various portions of textile element **40**. As discussed above, however, a wide-tube circular knitting machine is generally capable of forming various types of stitches within a single textile structure. The wide-tube cir-

US 8,266,749 B2

9

cular knitting machine may, therefore, vary the stitches within textile element **40** to produce various patterns, designs, or textures, for example. Various types of stitches may also be formed with other types of knitting machines. With reference to FIG. **10**, a textile element **40'** with the general shape of textile element **40** is depicted as having various areas with different textures. For example, a central area that corresponds with instep region **33** has a first texture **46'** that is generally smooth. In addition, textile element **40'** includes a second texture **47'** that is a plurality of longitudinal ribs. When incorporated into footwear **10**, the ribs will extend longitudinally along lateral region **31** and medial region **32**, and the ribs may extend into heel region **35**. The ribs may be present for aesthetic purposes, or may affect the stretch properties of upper **20**, for example. Accordingly, textile element **40'** exhibits areas with different textures in a single element of textile material.

Many conventional articles of footwear incorporate uppers with various material elements that each exhibit different properties. For example, a first material element may be smooth, and a second material element may be textured. The first and second material elements are then stitched together to form a portion of the conventional upper. Textile element **40'** also exhibits smooth and textured areas. In contrast with the conventional upper, however, first texture **46'** and second texture **47'** are incorporated into a single, unitary element of textile, rather than two separate elements that are stitched or otherwise joined together.

A textile structure **40''** is depicted in FIG. **11** and has the general shape of both textile element **40** and textile element **40'**. Textile element **40''** includes areas with three different textures. A first texture **46''** is generally smooth and has the configuration of various strips that extends laterally across areas corresponding with lateral region **31**, medial region **32**, and instep region **33**. Various portions of textile element **40''** also include a second texture **47''**, which is generally rough in comparison with first texture **46''**. In addition, the area of textile element **40''** corresponding with instep region **33** includes a third texture **48''**. The different textures **46''-48''** are formed by merely varying the type of stitch formed by the wide-tube circular knitting machine at each location of textile element **40''**. Textures **46''-48''** may exhibit aesthetic differences, or the differences may be structural. For example, the degree of stretch in areas with textures **46''-48''** may be different, or the wear resistance of the areas may vary depending upon the stitch utilized. The air-permeability of textile element **40''** may also vary in the different areas. Third texture **48''** is formed to include a plurality of apertures that extend through textile element **40''**. The apertures may be formed by omitting stitches at specific locations during the wide-tube circular knitting process, and the apertures facilitate the transfer of air between the void within upper **20** and the area outside of upper **20**. Accordingly, the various stitches formed in textile element **40''**, or one of textile elements **40** or **40'**, may be utilized to vary the texture, physical properties, or aesthetics of footwear **10** within a single, unitary element of material.

In addition to varying the stitch types to form textures **46'-47'** and **46''-48''**, the type of yarn utilized in various areas of textile elements **40'** and **40''** may be changed to impart different properties. As discussed above, yarn may be formed from cotton, wool, elastane, rayon, nylon, and polyester, for example. Each of these yarn types may impart differing properties to the areas corresponding with textures **46'-47'** and **46''-48''**. For example, elastane may be utilized to impart stretch, wool may be utilized for insulation, and nylon may be utilized for durability. Accordingly, different yarn types may

10

be utilized to impart different properties. The types of knitting that may be utilized to form different zones with different properties (e.g., yarn characteristics, textures, etc.) may vary significantly to include the various warp knitting and weft knitting processes discussed earlier, such as tricot, raschel, double needle-bar raschel, circular knitting, and flat knitting, for example.

An article of footwear **110** is depicted in FIG. **12** and includes a sole structure **120** and an upper **130**. Upper **130** includes a textile element **140** having the general configuration of textile element **40**. As with textile element **40**, textile element **140** forms both an exterior surface and an interior surface of upper **130**. In addition, upper **130** includes a lace **131** and a plurality of elements **132-135** that also form a portion of the exterior surface. Lace **131** extends through a plurality of apertures formed in textile element **140**. The apertures may be formed by omitting stitches at specific locations. Element **132** is positioned in a forefoot area of footwear **110** and may be formed of leather or rubber, for example, to provide additional wear-resistance. Element **133** extends around the ankle opening to reinforce and limit stretch in the area of the ankle opening. Element **134** extends around the heel region to counter movement of the heel and seat the heel above sole structure **120**. Furthermore, elements **135** are substantially inextensible strips of material, such as leather or synthetic leather, that limit stretch on the lateral side of footwear **110**. Whereas upper **30** was almost exclusively formed by textile element **40**, upper **130** also includes lace **131** and elements **132-135**. Accordingly, an upper in accordance with the present invention may incorporate a plurality of additional components.

Another article of footwear **210** is depicted in FIGS. **13-14** and includes a sole structure **220** and an upper **230**. Upper **230** includes a textile element **240** that forms an interior layer. In addition, upper **230** includes an intermediate layer **250** and an exterior layer **260**. As discussed in the Background of the Invention section above, the upper of a conventional article of footwear may be formed from multiple material layers that include an exterior layer, an intermediate layer, and an interior layer. The materials forming the exterior layer of the upper may be selected based upon the properties of wear-resistance, flexibility, and air-permeability, for example. The intermediate layer of the upper may be formed from a lightweight polymer foam material that provides cushioning and protects the foot from objects that may contact the upper. Similarly, an interior layer of the upper may be formed of a moisture-wicking textile that removes perspiration from the area immediately surrounding the foot.

Upper **230** has a configuration that is similar to the configuration of the conventional upper in that various material layers are utilized. In contrast with the conventional upper, however, the interior layer is formed of textile element **240**, which is manufactured through the process discussed above. That is, textile element **240** is a single element of textile that forms the interior layer of upper **230**. A benefit to utilizing textile element **240** for the interior layer is that textile element **240** includes few seams that may contact the foot. In addition, the stitches utilized at various locations of textile element **240** may modify the texture of the interior surface of upper **230**, thereby limiting the degree of slip that occurs between the foot and upper **230** or enhancing the air-permeability of upper **230** in specific locations.

Various warp knitting or weft knitting processes may be utilized to form textile element **40**, or the various other textile elements discussed above. An advantage of this process is that various stitches may be incorporated into specific locations of textile element **40** to modify the physical properties or aes-

US 8,266,749 B2

11

thetics of textile element 40. Whereas a conventional upper includes various elements that stitched or adhesively joined, textile element 40 is a single, unitary element of material. From the perspective of manufacturing, utilizing multiple materials to impart different properties to an article of footwear may be an inefficient practice. By forming textile element 40 to be a single, unitary element of material, however, efficiency is increased in that upper 20 may include a single textile element, rather than numerous joined elements.

A variety of knitting processes may be utilized to form textile element 40, as discussed above. As a specific example, a jacquard double needle-bar raschel knitting machine may be utilized to form a flat textile structure, and may also be utilized to form the textile structure to have the configuration of a spacer mesh textile. Unlike textile structure 60, which exhibits a generally cylindrical configuration, the textile structure formed with the jacquard double needle-bar raschel knitting machine will have a flat configuration. Like textile structure 60, however, an outline of a textile element may be imparted to the textile structure formed with the jacquard double needle-bar raschel knitting machine. That is, differences in the stitches within the textile structure may form an outline with the shape and proportions of the intended textile element. Accordingly, the textile element may be removed from the textile structure and incorporated into footwear 10. In addition, the jacquard double needle-bar raschel knitting machine may be utilized to impart various textures, different properties, or different yarn types to the textile element. Similarly, other types of knitting, such as a flat knitting, may be utilized within the scope of the present invention to impart various textures, different properties, or different yarn types to the textile element.

The present invention is disclosed above and in the accompanying drawings with reference to a variety of embodiments. The purpose served by the disclosure, however, is to provide an example of the various features and concepts related to the invention, not to limit the scope of the invention. One skilled in the relevant art will recognize that numerous variations and modifications may be made to the embodiments described above without departing from the scope of the present invention, as defined by the appended claims.

We claim:

1. A method of manufacturing an article of footwear, the method comprising:

simultaneously knitting a textile element with a surrounding textile structure, the knitted textile element having at least one knitted texture that differs from a knitted texture in the surrounding knitted textile structure;
removing the knitted textile element from the surrounding knitted textile structure;
incorporating the knitted textile element into the article of footwear.

2. The method of claim 1, wherein simultaneously knitting a textile element with a surrounding textile structure includes simultaneously knitting a plurality of textile elements.

3. The method of claim 1, wherein simultaneously knitting a textile element with a surrounding textile structure includes knitting an outline of the knitted textile element.

4. The method of claim 3, wherein the outline has the shape and proportion of the knitted textile element.

5. The method of claim 1, wherein the knitted textile element has a substantially planar configuration upon removal from the surrounding knitted textile structure.

6. The method of claim 1, wherein the knitted textile element includes longitudinal edges formed when the knitted textile element is removed from the surrounding knitted textile structure.

12

7. The method of claim 6, wherein the longitudinal edges are joined together to define at least a portion of a void for receiving a foot.

8. The method of claim 1, wherein the knitted textile element has a plurality of different knitted textures formed by varying at least one of the stitch type and the yarn type.

9. The method of claim 1, wherein simultaneously knitting a textile element with a surrounding textile structure includes utilizing a wide-tube circular knitting machine.

10. The method of claim 1, wherein simultaneously knitting a textile element with a surrounding textile structure includes utilizing a jacquard double needle-bar raschel knitting machine.

11. The method of claim 1, wherein simultaneously knitting a textile element with a surrounding textile structure includes forming the knitted textile element to include a first area and a second area with a unitary construction, the first area being formed of a first stitch configuration, and the second area being formed of a second stitch configuration that is different from the first stitch configuration to impart varying textures to a surface of the knitted textile element.

12. The method of claim 1, wherein incorporating the knitted textile element into the article of footwear includes securing edges of the knitted textile element to form a seam that extends along a lower region of an upper and securing the upper to a sole structure.

13. A method of manufacturing an article of footwear, the method comprising:

knitting a first textile element and a second textile element simultaneously with knitting a surrounding textile structure, the first knitted textile element located within a first portion of the knitted textile structure, the second knitted textile element located within a second portion of the knitted textile structure,

varying at least one of the types of stitches or the types of yarns in the knitted textile structure to impart a texture to the first and second knitted textile elements different from a texture of the knitted textile structure extending between the first and second portions;

removing the first and second knitted textile elements from the knitted textile structure;

incorporating at least one of the first and second knitted textile elements into the article of footwear.

14. The method of claim 13, wherein knitting a first textile element simultaneously with a surrounding knitted textile structure includes knitting an outline of the first knitted textile element.

15. The method of claim 13, wherein the first and second knitted textile elements have substantially planar configurations upon removal from the surrounding knitted textile structure.

16. The method of claim 13, wherein the first knitted textile element includes longitudinal edges formed when the first knitted textile element is removed from the surrounding knitted textile structure.

17. The method of claim 16, wherein the longitudinal edges are joined together to define at least a portion of a void for receiving a foot.

18. The method of claim 16, wherein incorporating the first knitted textile element into the article of footwear includes securing the longitudinal edges of the first knitted textile element to form a seam that extends along a lower region of an upper.

19. The method of claim 13, wherein knitting the first and second knitted textile elements simultaneously with a surrounding knitted textile structure includes utilizing a wide-tube circular knitting machine.

US 8,266,749 B2

13

20. The method of claim **13**, wherein knitting the first and second textile knitted elements simultaneously with a surrounding knitted textile structure includes utilizing a jacquard double needle-bar raschel knitting machine.

21. The method of claim **13**, wherein knitting the first knitted textile element simultaneously with a surrounding knitted textile structure includes forming the first knitted textile element to include a first area and a second area with a

14

unitary construction, the first area being formed of a first stitch configuration, and the second area being formed of a second stitch configuration that is different from the first stitch configuration to impart varying textures to a surface of the first knitted textile element.

* * * * *